

WARNINGS:

Not suitable for children under 3 years of age
Maximum capacity of 30kgs
Adult supervision required at all times
Children should be instructed on how to apply brakes before use
This product should not be operated on public roads, highways or bicycle paths
Read 'Safe operation' section before use
Always inspect and maintain product prior to use

SAFE OPERATION:

This product must be assembled by an adult and checked by an adult before use
Ensure nuts and bolts remain securely fastened before use
Lubricate the chain often
Ensure the tyres are pumped up before use – use hand pump only (maximum 30PSI)
Perform a brake test before use
Do not store in direct sunlight

Material of products:

A、 (PP) B、 (IRON)

PEDAL GO-KART

Operating Instructions and Assembly Manual



Execution Standard: EN71

Please read this manual carefully before use

Caution: For correct and safe operation of this product, be sure to read this instruction manual carefully before use. Please retain this user manual for future reference.

Parts List (included):



1. One steering wheel
and steering wheel cover



2. One seat



5. One front panel



6. One license plate



3. One steering shaft



4. One steering support



7.
4 x M5*40mm bolts,
4 x M5*45mm bolts,
2 x M5*50mm bolts
4x 5*14washers
6x 5*12washers
10pcsxM5nuts
The extra for standby use:
1pc 5*14washer
1pc 5*12washer
1pcnut



8. Steering wheel cover

Assembly Instructions:

1. Attach the steering support to the frame of the go-kart. Fix with **M5*45mm** bolts and ensure to use washers where appropriate.



2. Fix the seat to the frame of the go-kart using **M5*40mm** bolts, ensure to use washers again where appropriate.



3. Insert the steering shaft through the turning pole. Place the front panel over the steering shaft.



4. Please pull this part when you are inserting the steering shaft through the turning pole.



Page6

5.put the black plastic-washers on the top of the front panel



6.Place the steering wheel in place and insert the steering shaft through it and fix with **2 square washers** and **M8 nut**.



Page7

7.Fix the **license** plate on the front of the go-kart with 2 x bolt 5*50mm and washers.



8.Place the steering wheel cover in the centre of the steering wheel.



9.Ensure all nuts and bolts are securely tightened before use, and the tyres are appropriately inflated.